Site Engineering Report

Hamilton Residence 40 Swifts Lane Darien, Connecticut

Prepared for:

James & Liane Hamilton 40 Swifts Lane Darien, CT 06820

Date Prepared: April, 2021

Prepared by:
DiVesta Civil Engineering, LLC

Table of Contents

Site Location Map

Site Engineering Report

Introduction

Existing Site Conditions

Project Description

Stormwater Management

Developed condition site runoff characteristics

Site Utilities

Sanitary Sewer

Water

Sedimentation & Erosion Control Narrative

Appendices

Appendix A:

Stormwater Management Operation and Maintenance Plan

Appendix B:

Water Quality Volume Calculations

Appendix C:

Web Soils

DiVesta Civil Engineering, LLC

40 Swifts Lane SUNSWYCK RD IST OF DARIEN 33 16D 35-A 37A 37 GOODWIVES RIVER RD 96 95A 95 GOODWIVES RIVER RD SALEM STRAITS RD pp Geo 1" = 200 ft

Property Information

Property ID 10510
Location 40 SWIFTS LANE
Owner HAMILTON JAMES &



MAP FOR REFERENCE ONLY NOT A LEGAL DOCUMENT

Town of Darien, CT makes no claims and no warranties, expressed or implied, concerning the validity or accuracy of the GIS data presented on this map.

Geometry updated 3/15/2021 Data updated 3/11/2021

Print map scale is approximate. Critical layout or measurement activities should not be done using this resource.

42

Introduction

This report has been prepared to present technical information in support of the construction of a pool, pool patio and spa at 40 Swifts Lane, Darien, CT. Other proposed activity associated with this construction will be minor regrading and the installation of a stormwater management system. The property is located on the east side of Swifts Lane in the R-1 Residence zone of Darien.

Existing Site Conditions

The property has a total lot area of 94,686± square feet or 2.1737± acres. The property is fully developed with the original house constructed in 1719 with a renovation completed in 2002 according to the Assessor's card. The access to the property is via paved driveway from Swifts Lane located parallel to the westerly property line.

The property is bordered by residential properties on three sides and Gorham's pond to the east.

The parcel slopes moderately to mildly from west to east. The property consists of manicured lawn east of the ornamental gardens that are around the existing house and there is a small wooded area east of the stonewall that parallels Gorham's Pond. There is a stonewall "seawall" that is located along the shore of Gorham's Pond with a break in the wall on the south end to be able to access Gorham's Pond. There are mature trees along the property boundaries and throughout the existing landscape.

There are no other wetlands on the property except for the edge of the water at Gorham's Pond.

The easterly portion of the site adjacent to Gorham's Pond has the one percent chance flood hazard line at elevation 10.7 according to the survey plan prepared by William W. Seymour & Associates, PC, Darien, CT

Project Description

The proposal for this site consists of constructing a pool, pool patio and spa. Other work associated with this project will include minor regrading associated with the pool, pool patio and the installation of a subsurface stormwater management system to handle the water quality volume from the impervious areas related to the proposed pool.

Stormwater Management Facilities

Existing Site Runoff Characteristics

Currently the runoff from the house roof areas discharges into the ground with the outlets unknown and runoff from the driveway sheet flows across the lawn area in an easterly direction which ultimately flows to Gorham's Pond.

Developed Condition Site Runoff Characteristics

The proposed grading for the pool and pool patio will not change the overall drainage pattern. Once the regrading is completed the drainage pattern will be the same. Due to the property being located on Gorham's Pond which flows into Long Island Sound detention is not required. We are proposing to collect the water quality volume from the proposed pool and pool patio and treat the water quality volume. There will be one subsurface bio-retention area consisting of Cultec C-4 chambers to store the water quality volume from the proposed impervious areas. The water quality volume consists of the first inch of runoff. All other runoff from the site will sheet flow onto the ground and ultimately flow to Gorham's Pond.

The water quality volume for the proposed pool and pool patio will require a total of 156 cubic feet of storage for the first inch of runoff. The proposed subsurface bio-retention area consisting of Cultec C-4 chambers will have a total volume of 180 cubic feet of storage. This volume is equal to or greater than the water quality volume.

Per Section 880 of the Darien Zoning Regulations we are requesting a waiver of the requirements of Section 880 for a detailed stormwater management plan and drainage plan.

Site Utilities

Sanitary Sewer

The existing residence is connected to the sanitary sewer located in Swifts Lane via grinder pump.

Water

The site is connected to the municipal water main located in Swifts Lane.

Sedimentation & Erosion Control Narrative

Reference is made to the Sedimentation and Erosion Control Plan drawing, which, along with this text is included in the report, part of the Sedimentation and Erosion Control Plan for this project. All erosion controls are to follow the 2002 CT Guideline for Soil Erosion and Sediment Control.

Sedimentation and erosion controls for the lot will consist of silt fence placed on the down gradient side of all cut and fill areas and the installation of anti-tracking pads at the entrance of the construction access to the pool and pool patio. Sedimentation and erosion controls shown on the plan are specific to this property.

Hamilton Residence

Appendix A: Stormwater Management Operation and Maintenance

Plan

DiVesta Civil Engineering, LLC

Stormwater Management Operation and Maintenance Plan For

40 Swifts Lane Darien, Connecticut

April 30, 2021

The object of the stormwater management operation and maintenance plan is three fold; 1) is to collect the runoff from the proposed pool patio and convey the runoff into the subsurface bioretention system, 2) once the runoff has been collected and conveyed to the subsurface bioretention system the runoff will infiltrate into the surrounding soil, 3) the treatment system will detain the water quality volume of runoff from the pool patio before infiltrating into the surrounding soil before discharging into Gorham Pond.

Maintenance Measures

- 1. Inspect the channel drain and junction boxes sumps annually for any accumulation of sediment. If there is any accumulated sediment it shall be removed by hand.
- 2. Inspect annually the channel drain to ensure that it is clear and free of buildup debris and that there are no blockages and that the pipes are free flowing.
- 3. Removal of any accumulated sediment will ensure that the bio-retention systems will function properly.

Hamilton Residence

Appendix B: Water Quality Volume Calculations

DiVesta Civil Engineering, LLC

Water Quality Volume (WQV) <u>Calculations</u>

Hamilton Residence 40 Swifts Lane Darien, Connecticut Dated: April 28, 2021

Water Quality Volume Calculations

Water Quality Volume (WQV) = ((1") (R) (A)) / 12Where: A = total area in square feet R = 0.05 + 0.009 (I)I = percent impervious cover

Proposed Site Sub Catchment # 1: Available Storage = 180 cu-ft

A = 2,067 sf (pool, pool patio) I = 95%

R = 0.05 + 0.009 (95%)R = 0.905

WQV = ((1") (R) (A)) / 12 WQV = ((1") (0.905) (2,067 sf)) / 12 WQV = 156 cu-ft (required)

Hamilton Residence

Appendix C: Web Soils

DiVesta Civil Engineering, LLC

Natural Resources Conservation Service


USDA

41° 3' 29" N

Web Soil Survey National Cooperative Soil Survey

5/3/2021 Page 1 of 3

Very Stony Spot Stony Spot Spoil Area Wet Spot Other W 8 0 Soil Map Unit Polygons Area of Interest (AOI) Soil Map Unit Points Soil Map Unit Lines Area of Interest (AOI) Soils









Special Point Features

Blowout

9

Borrow Pit

Clay Spot







Closed Depression



Gravelly Spot

Gravel Pit



Marsh or swamp

Lava Flow

Landfill

Mine or Quarry

Miscellaneous Water

Perennial Water

Rock Outcrop Saline Spot Sandy Spot

Aerial Photography

Please rely on the bar scale on each map sheet for map

measurements.

contrasting soils that could have been shown at a more detailed

misunderstanding of the detail of mapping and accuracy of soil

line placement. The maps do not show the small areas of

Enlargement of maps beyond the scale of mapping can cause

Warning: Soil Map may not be valid at this scale.

The soil surveys that comprise your AOI were mapped at

MAP INFORMATION

Source of Map: Natural Resources Conservation Service Web Soil Survey URL:

Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator distance and area. A projection that preserves area, such as the projection, which preserves direction and shape but distorts Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required. This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Version 20, Jun 9, 2020 State of Connecticut Survey Area Data: Soil Survey Area:

Soil map units are labeled (as space allows) for map scales 1:50,000 or larger. Date(s) aerial images were photographed: Jul 21, 2014—Aug

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.

Severely Eroded Spot

Slide or Slip

Sinkhole

Sodic Spot

Map Unit Legend

Map Unit Symbol	Map Unit Name	Acres in AOI	Percent of AOI
73C	Charlton-Chatfield complex, 0 to 15 percent slopes, very rocky	2.5	48.0%
73E	Charlton-Chatfield complex, 15 to 45 percent slopes, very rocky	1.7	32.6%
W	Water	1.0	19.3%
Totals for Area of Interest		5.3	100.0%

State of Connecticut

73C—Charlton-Chatfield complex, 0 to 15 percent slopes, very rocky

Map Unit Setting

National map unit symbol: 2w698

Elevation: 0 to 1,550 feet

Mean annual precipitation: 36 to 71 inches Mean annual air temperature: 39 to 55 degrees F

Frost-free period: 140 to 240 days

Farmland classification: Not prime farmland

Map Unit Composition

Charlton, very stony, and similar soils: 50 percent Chatfield, very stony, and similar soils: 30 percent

Minor components: 20 percent

Estimates are based on observations, descriptions, and transects of

the mapunit.

Description of Charlton, Very Stony

Setting

Landform: Hills, ridges

Landform position (two-dimensional): Backslope, shoulder, summit Landform position (three-dimensional): Crest, side slope, nose

slope

Down-slope shape: Linear, convex Across-slope shape: Convex

Parent material: Coarse-loamy melt-out till derived from granite,

gneiss, and/or schist

Typical profile

Oe - 0 to 2 inches: moderately decomposed plant material

A - 2 to 4 inches: fine sandy loam

Bw - 4 to 27 inches: gravelly fine sandy loam C - 27 to 65 inches: gravelly fine sandy loam

Properties and qualities

Slope: 3 to 15 percent

Surface area covered with cobbles, stones or boulders: 1.6 percent

Depth to restrictive feature: More than 80 inches

Drainage class: Well drained

Runoff class: Low

Capacity of the most limiting layer to transmit water (Ksat): Moderately low to high (0.14 to 14.17 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Maximum salinity: Nonsaline (0.0 to 1.9 mmhos/cm) Available water capacity: Moderate (about 8.7 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 6s

Hydrologic Soil Group: B

Ecological site: F144AY034CT - Well Drained Till Uplands

Hydric soil rating: No

Description of Chatfield, Very Stony

Setting

Landform: Ridges, hills

Landform position (two-dimensional): Backslope, shoulder, summit

Landform position (three-dimensional): Crest, side slope, nose

slope

Down-slope shape: Convex

Across-slope shape: Linear, convex

Parent material: Coarse-loamy melt-out till derived from granite,

gneiss, and/or schist

Typical profile

Oi - 0 to 1 inches: slightly decomposed plant material

A - 1 to 2 inches: fine sandy loam

Bw - 2 to 30 inches: gravelly fine sandy loam

2R - 30 to 40 inches: bedrock

Properties and qualities

Slope: 3 to 15 percent

Surface area covered with cobbles, stones or boulders: 1.6 percent

Depth to restrictive feature: 20 to 41 inches to lithic bedrock

Drainage class: Well drained

Runoff class: High

Capacity of the most limiting layer to transmit water (Ksat): Very low

(0.00 to 0.00 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Maximum salinity: Nonsaline (0.0 to 1.9 mmhos/cm) Available water capacity: Low (about 4.3 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 6s

Hydrologic Soil Group: B

Ecological site: F144AY034CT - Well Drained Till Uplands

Hydric soil rating: No

Minor Components

Sutton, very stony

Percent of map unit: 5 percent

Landform: Ground moraines, hills

Landform position (two-dimensional): Footslope Landform position (three-dimensional): Base slope

Down-slope shape: Concave Across-slope shape: Linear Hydric soil rating: No

Rock outcrop

Percent of map unit: 5 percent Hydric soil rating: No

Hollis, very stony

Percent of map unit: 5 percent
Landform: Ridges, hills
Landform position (two-dimensional): Backslope, shoulder, summit
Landform position (three-dimensional): Crest, side slope, nose
slope

Down-slope shape: Convex

Across-slope shape: Linear, convex

Hydric soil rating: No

Leicester, very stony

Percent of map unit: 5 percent Landform: Drainageways, depressions Down-slope shape: Linear Across-slope shape: Concave Hydric soil rating: Yes

Data Source Information

Soil Survey Area: State of Connecticut Survey Area Data: Version 20, Jun 9, 2020